

# ActivPanel Nickel with USB-C



#### **DISPLAY**

Diagonal Size	65" 4K, 75" 4K, 86" 4K	
Screen Type	TFT LCD (Direct LED Backlight)	
Aspect Ratio	16:9	
Display Area	65" 4K: 1429 x 804 mm (56.3 x 31.7 in) 75" 4K: 1652 x 930 mm (65 x 36.6 in) 86" 4K: 1895 x 1066 mm (74.6 x 41.9 in)	
Display Colours	1.07 Billion	
Resolution	4K UHD (3840 x 2160 @ 60 Hz)	
Response Time	8 ms	
Panel Refresh Rate	60 Hz	
LED Lifespan	50,000 hours	
LCD Viewing Angle	178°	
Brightness	65" 4K: 350 cd/m2 75" 4K: 350 cd/m2 86" 4K: 400 cd/m2	
Contrast Ratio	4000:1	
Ambient Light Sensor	Yes	
Glass Hardness	9H (Pencil), 7 (Mohs)	
Glass Type	Heat-tempered, Anti-Glare	

#### **INTERACTIVITY**

Front Facing Controls	Yes, with Power, Menu, Volume Controls, Source Selection
Touch Technology	Vellum™ Writing Technology
Continuous Touch Points	15
Touch Resolution	32768 x 32768 px
Response Time	10 ms
Touch Accuracy	1 mm
Tracking Rate	4 m/s
Scan Rate	100 Hz
Gestures and Edge Swipes	Windows® Supported
Pens Included	1
Pen Type	Battery-less Pen
Pen Holder	Integrated Full-length Pen Tray
Pen Tip Diameter	3 mm
Pen and Touch Differentiation	No
Palm Detection	Yes
Annotation Over Any Source	Yes
Classroom Essential Apps	Including Whiteboard, Annotate, Timer, Spinner, Screen Capture, Screen Share, Browser, PDF Reader, Media Players
Compatibility	Windows® 8 to 10; OS X® 10.8 to 10.11 macOS® Sierra 10.12.1 or later; Linux® Ubuntu® 18.04 LTS; Chrome OS™

#### **CONNECTIVITY**

HDMI® 2.0 In (Rear)	1	
HDMI 2.0 In (Front)	1	
VGA In	1	
VGA Audio In	1	
USB-A 2.0 (Rear)	1	
USB-A 2.0 (Front)	1	
USB-A 3.0 (faster data transfer, Front)	1 (OPS)	
USB-B Touch (Rear)	1	
USB-B Touch (Front)	1	
USB-C PD2.0, USB 2.0, DP1.2 (Rear)	1	
LAN In (RJ45)	1x 10/100 Mbps	
LAN Out (RJ45)	1x 10/100 Mbps	
Wake-on-LAN	Yes	
Wi-Fi® Module IEEE® 802.11a/b/g/n/ac	Included	
Wireless, 2x2		
RS-232	Yes	
CVBS	1	
Mic In (3.5 mm)	1	
Headphone	1	
OPS Slot	1	

#### **COMPUTING**

Operating System	Android™ Oreo 8
RAM	2 GB
Internal Storage	16 GB
CPU	Quad Core: (2) ARM Cortex A73, (2) ARM Cortex A53
GPU	ARM Mali-G51 MP2
Remote Over-the-Air Updates	Yes
Promethean Panel Management	Yes

#### **AUDIO**

Page 1



### Nickel with USB-C

#### **POWER**

Power Requirements	100V - 240V AC
Power Consumption (Typical)	65" 4K: 107W 75" 4K: 107W 86" 4K: 159W
Power Consumption (Standby)	<=0.5 W
Ultra-Quiet Fanless Design	Yes

#### **ENVIRONMENTAL**

Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-15°C to 55°C (-5°F to 131°F)
Operating Humidity	20% to 80% non-condensing humidity
Storage Humidity	20% to 90% non-condensing humidity

#### PHYSICAL SPECIFICATIONS

Panel Dimensions	65" 4K: 1536 x 960 x 90 mm (60.5 x 37.8 x 3.5 in) 75" 4K: 1767 x 1093 x 106 mm (69.6 x 43.0 x 4.2 in) 86" 4K: 2018 x 1236 x 113 mm (79.4 x 48.7 x 4.4 in)
Packed Dimensions	65" 4K: 1720 x 1095 x 272 mm (67.7 x 43.1 x 10.7 in) 75" 4K: 1880 x 1160 x 320 mm (74.0 x 45.7 x 12.6 in) 86" 4K: 2140 x 1340 x 280 mm (84.3 x 52.8 x 11.0 in)
Net Weight	65" 4K: 46 kg (101 lbs) 75" 4K: 62 kg (137 lbs) 86" 4K: 82 kg (181 lbs)
Packed Weight	65" 4K: 57 kg (126 lbs) 75" 4K: 77 kg (170 lbs) 86" 4K: 100 kg (220 lbs)
Wall Mount Dimensions	1010 x 720 x 52 mm (39.8 x 28.3 x 2.0 in)
VESA Mount Point	65" 4K: 600 x 400 mm (23.6 x 15.7 in) 75" 4K: 600 x 400 mm (23.6 x 15.7 in) 86" 4K: 700 x 400 mm (27.6 x 15.7 in)

#### **COMPLIANCE & CERTIFICATION**

Regulatory Certifications	CE, FCC, IC, UL, CUL, CB, RCM
Energy Star Certified	65" 4K: Yes 75" 4K: Yes 86" 4K: Yes

#### **EDUCATION SOFTWARE LICENCE**

ActivInspire® Professional	Included
Single User	

#### **PACKED CONTENTS**

What's in the Box (1)	(1) ActivPanel Nickel	
	(1) 3M Length HDMI Cable	
	(1) 3M Length USB Cable (A-B)	
	(1) 3M Regional Power Cable	
	(1) 2M Length USB-C Cable	
	(1) Remote Control	
	(2) Batteries for Remote Control	
	(1) ActivPanel Nickel Pen	
	(1) Sealed Antistatic Bag	
	(4) VESA mount screws (M6)	
	(1) Mini PC Bracket with screws	
	(1) Quick Install Guide	
What's in the Box (2)	(1) Promethean Wi-Fi Module (Ni/Co)	
	(2) Antenna	
	(1) Promethean Wi-Fi Module (Ni/Co)	
	User Guide	

#### **INSTALLATION**

The installation of this product should be completed by a qualified installer. Use of components not supplied by Promethean or not meeting minimum specifications may impact performance, safety and warranty. For more information, visit Support.PrometheanWorld.com.

#### WARRANTY

Warranty term and upgrade options vary by region. Contact your local reseller or distributor for information and visit PrometheanWorld.com/Warranty.


#### **SUPPORT**

 $For all \ Promethean \ products, \ visit \ Support. Promethean World. com.$ 





### Nickel with USB-C

#### **TECHNICAL DRAWINGS**



DIM	DIMENSIONS (MM)	DIMENSIONS (IN)
А	1641	64.6
В	1430	56.3
С	805	31.7
D	1101	43.3
Е	133	5.2
F	83	3.3
G	960	37.8
Н	1536	60.5
I	600	23.6
J Min	151	5.9
J Max	289	11.4
K Min	1151	45.3
K Max	1289	50.7
L	90	3.5






Page 3





### Nickel with USB-C

#### **TECHNICAL DRAWINGS**



DIM	DIMENSIONS (MM)	DIMENSIONS (IN)
А	1895	74.6
В	1652	65.0
С	929	36.6
D	1105	43.5
Е	144	5.7
F	76	3.0
G	1093	43.0
Н	1767	69.6
I	600	23.6
J Min	228	9.0
J Max	365	14.4
K Min	1228	48.3
K Max	1365	53.7
L	106	4.2






Page 4 Page 4





### Nickel with USB-C

#### **TECHNICAL DRAWINGS**



DIM	DIMENSIONS (MM)	DIMENSIONS (IN)
А	2177	85.7
В	1897	74.7
С	1067	42.0
D	1107	43.6
Е	155	6.1
F	78	3.1
G	1236	48.7
Н	2018	79.4
I	700	27.6
J Min	292	11.5
J Max	430	16.9
K Min	1292	50.9
K Max	1430	56.3
L	113	4.4





Page 5