

ActivPanel Titanium Pro



DISPLAY

Diagonal Size	70" 4K, 75" 4K, 86" 4K
Screen Type	TFT LCD (Direct LED Backlight)
Aspect Ratio	16:9
Display Area	70" 4K: 1541 x 868 mm (60.7 x 34.2 in) 75" 4K: 1652 x 930 mm (65 x 36.6 in) 86" 4K: 1895 x 1066 mm (74.6 x 41.9 in)
Display Colors	1.07 Billion
Resolution	4K UHD (3840 x 2160 @ 60 Hz)
Response Time	8 ms
Panel Refresh Rate	60 Hz
LED Lifespan	50,000 hours
LCD Viewing Angle	178°
Brightness	70" 4K: 380 cd/m2 75" 4K: 380 cd/m2 86" 4K: 400 cd/m2
Contrast Ratio	4000:1
Ambient Light Sensor	Yes
Glass Hardness	9H (Pencil), 7 (Mohs)
Glass Type	Heat-tempered, Anti-Glare

INTERACTIVITY	
Angled Center Console	Yes, with Power, Volume Control, Menu, Freeze, No Touch, Source Selection Buttons
Touch Technology	Vellum™ Writing Technology
Continuous Touch Points	20
Touch Resolution	32768 x 32768 px
Response Time	≤5 ms
Touch Accuracy	1 mm
Tracking Rate	6 m/s
Scan Rate	200 Hz
Gestures and Edge Swipes	Windows® Supported
Eraser Included (Block Eraser)	1
Pens Included	4 with Rear Erasing Feature
Pen Type	Battery-less Pen
Pen Holder	Integrated Full-length Pen Tray
Pen Tip Diameter	3 mm
Pen and Touch Differentiation	Yes
Pen Identities	2
Palm Detection	Yes
Annotation Over Any Source	Yes
Productivity Apps	Including Whiteboard, Annotate, Timer, Spinner, Screen Capture, Screen Share, Browser, PDF Reader, Media Players
Compatibility	Windows® 8 to 10; OS X® 10.8 to 10.11 macOS® Sierra 10.12.1 or later; Linux® Ubuntu® 18.04 LTS; Chrome OS™

CONNECTIVITY

OPS Slot	1
HDMI® In (Rear)	2 (2.0)
HDMI In (Front)	1 (2.0)
USB-A 2.0 (Rear)	2
USB Touch (Type B) (Rear)	3
USB Touch (Type B) (Front)	1
USB-A 3.0 (faster data transfer) (Rear)	2
USB-A 3.0 (faster data transfer)	2
(Front)	
LAN In (RJ45)	1x 10/100/1000 Mbps
LAN Out (RJ45)	1x 10/100/1000 Mbps
RS-232	Yes
Wake-on-LAN	Yes
Wi-Fi [®] Module	Included, IEEE® 802.11a/b/g/n/ac Wireless, 2x2
Bluetooth®	Yes (4.2)
DP In	1 (1.2)
HDMI Out	1 (2.0)
VGA In	1
VGA Audio In	1
CVBS	1
Mic In (3.5 mm)	1
Headphone	1
Proximity Sensor for Warm Boot	Yes

INTERNAL COMPUTING

Operating System	Android™ Oreo 8
RAM	4 GB
Internal Storage	64 GB (32 GB x2)
CPU	Quad Core: (2) ARM Cortex A73, (2) ARM Cortex A53
GPU	ARM Mali-G51 MP4

Optional OPS-M COMPUTING

Device Type	Open Pluggable Specification (OPS)
Operating System	Windows 10 Pro
CPU	10th Gen Intel Core i7
GPU	Intel UHD Graphics (supports 4K @ 60 Hz)
RAM	16 GB DDR4x2, 2666MHz
Internal Storage	256 GB SSD, PCI-e, M.2
Touchscreen Compatibility	Yes

ActivPanel Ti Pro Workplace SS 09/21 v1.8 EN



Titanium Pro

AUDIO

Dual Front Facing,	65+" 4K: 2 x15 Watts
Bass Enhanced	
Speakers	75" 4K: 2 x15 Watts 86" 4K: 2 x 20 Watts

POWER

Power Requirements	100V - 240V AC
Power Consumption (Maximum)	70" 4K: 215W 75" 4K: 280W 86" 4K: 370W
Power Consumption (Standby)	<=0.5 W
Ultra-Quiet Fanless Design	Yes

ENVIRONMENTAL

Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-15°C to 55°C (-5°F to 131°F)
Operating Humidity	20% to 80% non-condensing humidity
Storage Humidity	20% to 90% non-condensing humidity

PHYSICAL SPECIFICATIONS

Panel Dimensions	70" 4K: 1668 x 1033 x 95 mm (65.7 x 40.7 x 3.7 in) 75" 4K: 1764 x 1089 x 109 mm (69.4 x 42.9 x 4.3in) 86" 4K: 2014 x 1231 x 109 mm (79.3 x 48.5 x 4.3 in)
Packed Dimensions	70" 4K: 1796 x 1145 x 278 mm (70.7 x 45.1 x 11.0 in) 75" 4K: 1895 x 1200 x 278 mm (74.6 x 47.2 x 11.0in) 86" 4K: 2140 x 1350 x 278 mm (84.3 x 53.1 x 11.0in)
Net Weight	70" 4K: 53 kg (117 lbs) 75" 4K: 60 kg (132 lbs) 86" 4K: 75 kg (165 lbs)
Packed Weight	70" 4K: 75.5 kg (166.4 lbs) 75" 4K: 85.5 kg (188.5 lbs) 86" 4K: 101.6 kg (224.0 lbs)
Wall Mount Dimensions	1010 x 720 x 52 mm (39.8 x 28.3 x 2.0 in)
VESA Mount Point	70" 4K: 600 x 400 mm (23.6 x 15.7 in) 75" 4K: 800 x 400 mm (31.5 x 15.7 in) 86" 4K: 800 x 400 mm (31.5 x 15.7 in)

COMPLIANCE & CERTIFICATION

Regulatory Certifications	CE, FCC, IC, UL, CUL, CB, RCM
Energy Star Certified	70" 4K: Yes 75" 4K: Yes 86" 4K: Yes

PACKED CONTENTS

ACKED CONTENTS	
hat's in the Box	(1) ActivPanel (1) 3M Length HDMI Cable (1) 3M Length USB cable (A-B) (1) 3M Regional Power Cable (1) Remote Control (2) Batteries for Remote Control (4) ActivPanel Pens (1) Block Eraser (1) Sealed Antistatic Bag (4) VESA mount screws (M6) (1) Mini PC Bracket with screws (1) Quick Install Guide (1) Promethean Wi-Fi/Bluetooth Module (Ti) (2) Antenna (1) Promethean Wi-Fi/Bluetooth Module (Ti) User Guide
	(1) Wall Mount

INSTALLATION

The installation of this product should be completed by a qualified installer. Use of components not supplied by Promethean or not meeting minimum specifications may impact performance, safety and warranty. For more information, visit Support.PrometheanWorld.com.

WARRANTY

Warranty term and upgrade options vary by region. Contact your local reseller or distributor for information and visit PrometheanWorld.com/Warranty.

SUPPORT

 $For all\ Promethean\ products, visit\ Support. Promethean\ World. com.$




Titanium Pro

TECHNICAL DRAWINGS


70"


Front



768 541 67	70.0 60.7
	60.7
67	
	34.1
107	43.6
36	5.4
57	2.6
033	40.7
568	65.7
00	23.6
57	6.2
95	11.6
157	45.6
	51.0
295	31.0
	5668 00 57 95

Back








Titanium Pro

TECHNICAL DRAWINGS


75"


Front



DIMENSIONS	DIMENSIONS
(MM)	(IN)
1894	75.6
1651	65.0
928	36.5
1103	43.4
133	5.2
67	2.6
1089	42.9
1764	69.4
800	31.5
214	8.4
352	13.9
1215	47.8
1353	53.3
109	4.3
	(MM) 1894 1651 928 1103 133 67 1089 1764 800 214 352 1215 1353

Back





Side





Titanium Pro


TECHNICAL DRAWINGS

Front DIMB

DIM	DIMENSIONS (MM)	DIMENSIONS (IN)
А	2176	85.6
В	1896	74.7
С	1067	42.0
D	1107	43.6
Е	134	5.3
F	67	2.6
G	1231	48.5
Н	2014	79.3
I	800	31.5
J Min	286	11.3
J Max	424	16.7
K Min	1286	50.6
K Max	1424	56.1
L	109	4.3







Back